

TORQUE MOTOR

TMM0175-150

PERFORMANCE		Winding codes	3TAN	3UBS
		UNIT	FREE AIR CONVECTION (with glued stator)	FREE AIR CONVECTION (with glued stator)
Tp	Peak torque	Nm	339	339
Tc	Continuous torque	Nm	67.1	67.9
Ts	Stall torque	Nm	50.7	51.3
Kt	Torque constant	Nm/Arms	17.9	7.23
Ku	Back EMF constant (*)	Vrms/(rad/s)	10.3	4.18
Km	Motor constant	Nm/√W	3.94	3.98
R20	Electrical resistance at 20°C (*)	Ohm	13.8	2.20
L1	Electrical inductance (*)	mH	111	18.1
Ip	Peak current	Arms	27.1	66.9
Ic	Continuous current	Arms	3.99	9.97
Is	Stall current	Arms	3.02	7.56
Pc	Max. continuous power dissipation	W	463	463

SPECIFICATIONS		UNIT		
Udc	Nominal input voltage	VDC	600	600
τth	Thermal time constant	s	1810	1810
Rth	Thermal resistance	K/W	0.227	0.227
2p	Number of poles	-	22	22
J	Rotor inertia	kg.m ²	0.0136	0.0136
Mr	Rotor mass	kg	4.99	4.99
Ms	Stator mass	kg	13.7	13.7
Td	Max. detent torque (average to peak)	Nm	2.9	2.9
ns	Stall speed	rpm	0.030	0.030

Notes: (*) terminal to terminal. Ambient temperature = 20 °C. Max. coil temperature = 130 °C.
 Hypothesis and tolerances are in ETEL's Handbook. Stator connected to a total surface of 0.25 m² and rotor to a total surface of 0.094 m²

Caution: Any use of the motor beyond speed/force limit could lead to hazardous voltage and serious injuries. Customer is responsible for setting safeties/limitations that will keep the motor in its safe operating area. ETEL cannot be held responsible if the motor is used in an improper way.

