

TORQUE MOTOR

TML0291-050

PERFORMANCE		Winding codes	3TBN	3TDS
		UNIT	FREE AIR CONVECTION	FREE AIR CONVECTION
Tp	Peak torque	Nm	416	416
Tc	Continuous torque	Nm	84.4	84.4
Ts	Stall torque	Nm	64.1	64.1
Kt	Torque constant	Nm/Arms	14.2	7.08
Ku	Back EMF constant (*)	Vrms/(rad/s)	8.20	4.10
Km	Motor constant	Nm/√W	6.11	6.11
R20	Electrical resistance at 20°C (*)	Ohm	3.58	0.895
L1	Electrical inductance (*)	mH	29.1	7.27
Ip	Peak current	Arms	46.0	91.9
Ic	Continuous current	Arms	6.22	12.4
Is	Stall current	Arms	4.71	9.42
Pc	Max. continuous power dissipation	W	297	297

SPECIFICATIONS		UNIT		
Udc	Nominal input voltage	VDC	600	600
τth	Thermal time constant	s	3470	3470
Rth	Thermal resistance	K/W	0.370	0.370
2p	Number of poles	-	44	44
J	Rotor inertia	kg.m ²	0.0395	0.0395
Mr	Rotor mass	kg	3.46	3.46
Ms	Stator mass	kg	12.2	12.2
Td	Max. detent torque (average to peak)	Nm	1.9	1.9
ns	Stall speed	rpm	0.0079	0.0079

Notes: (*) terminal to terminal. Ambient temperature = 20 °C. Max. coil temperature = 130 °C.
 Hypothesis and tolerances are in ETEL's Handbook. Stator connected to a total surface of 0.14 m² and rotor to a total surface of 0.082 m²

Caution: Any use of the motor beyond speed/force limit could lead to hazardous voltage and serious injuries. Customer is responsible for setting safeties/limitations that will keep the motor in its safe operating area. ETEL cannot be held responsible if the motor is used in an improper way.

